Kelin tile grout is a new product for home decoration, which is totally instead of the sewing agent. At the same time, it is mould proof, moisture proof, environmental friendly, non-toxic and net flavor, adding negative oxygen ion to purify air. More importantly, without being continuously exposed to high intensity of sunlight, the product will not be yellowing, easy to clean and resistant to dirt. Australia joint research and development products to make the better performance, and through the Chinese Academy of Sciences strategic quality control guidance, to make products' quality stable. The tile grout is very easy to construction.

Main Ingredient	Epoxy resin, High-end color powder
Function	The filling and beautification of tile gap
Shelf Life	Stock in a cool and dry place at 0-37 °C for 18 months
Net Weight	450 ML
Packing	30 Sets/Carton


The product can be better used in the joints of ceramic tile, stone, glass, mosaic tile on the wall or floor in bathroom, kitchen, bedroom and so on. It has great varieties of color, bright luster and the surface is bright as porcelain after curing. Kelin a high quality **epoxy tile grout factory**. Welcome to contact us.



Varieties of colors for your choice. Also provide custom colors.



Provide Whole Room Gap Solution



Brief Construction Process











Clean the tiles and keep Polish with tile wax it dry. Polish with tile wax except the glazed tile.

Open & Watch, both sides can extruded meanwhile.

Screw on the nozzle, put Inclined cut the top of on the grout gun. the nozzle in 45°.











Squeeze out 60-80cm long grout in the forepart.

Evenly squeeze out the tile agent along the gap.


Press the grout with professional glue-press tools.

Don't touch in 4-5 hours and remove excess grout hours. Keep the tiles dry in 24 then

Professional Joint-Pressing Tool



Company Advantage



Factory Overview



Certification

